			ι
	[73]	Assign	ee: D
	[21]	Appl. ?	Vo.: 0
	[22]	Filed:	n
	[52]	Int. Cl. U.S. C. Field o	l
	[56]		
			U.S.
	3	3.220,392	11/19
		1.572.114	2/19
Ţ		1.088.384	8/19
		.117.790	6/19
M		.146,890	9/19
		.150,678	9/19 2/19
æ		.404.851	4/19
		.406.918	
Til.	5	,460,131	10/19
	5	,460,131	10/19
	5	,460,131	10/19

	[54]	MULTI-CYCLE, ENGINE BRAKING WITH POSITIVE POWER VALVE ACTUATION CONTROL SYSTEM AND PROCESS FOR USING THE SAME						
	[75]	Inventors: Gheorghe Cosma, Windsor; James Usko, North Granby, both of Conn.						
	[73]	73] Assignee: Diesel Engine Retarders, Inc., Wilmington, Del.						
	[21]	[21] Appl. No.: 08/997,610						
	[22]	Filed:	Dec.	23. 1997				
	[51] Int. Cl." F02D 13/04							
		[52] U.S. CI. 123/321						
	[58]	Field o	f Search	123/320, 321, 123/322				
	[56]	[56] References Cited						
			U.S. PA	TENT DOCUMENTS				
	3	.220,392	11/1965	Cummins				
		.572.114	2/1986					
		.688.384						
		.117.790		Clarke et al				
		150,678		Wittmann et al 123/321				
		183,018		Vittorio et al				
		.404,851						
-		.406,918		Joko et al				
din.	5,	.460.131	10/1995	Usko et al 123/321				

5,477,824	12/1995	Reedy	
5,479,890	1/1996	Freiburg et al.	
5,537,976	7/1996	Hu.	
5,586,531	12/1996	Vittorio .	
5,619,965	4/1997	Cosma et al	
5,626,116	5/1997	Reedy et al	
5,680,341	10/1997	Hu	123/321
5,692,469	12/1997	Rammer et al.	123/321
5,724,939	3/1998	Faletti et al.	123/321
5,803,038	9/1998	Ihara et al	123/321
5,816,216	10/1998	Figushira et al.	123/321
5,829,397	11/1998	Vorih et al	123/321
5.839,453	11/1998	Hu	123/321

Primary Examiner-Erick R. Solis Attorney, Agent. or Firm-Collier, Shannon, Rill & Scott, PLLC

ABSTRACT [57]

An apparatus and method for effectuating multi-cycle engine braking is disclosed. The present invention controls the operation of the engine valves to permit more than one compression release event during a single engine operating cycle. The apparatus includes an assembly for operating at least one exhaust valve of an engine cylinder during a positive power operation. The apparatus further includes an assembly for operating at least one intake valve of the engine cylinder. The apparatus further including an assembly for operating the at least one exhaust valve during an engine braking operation.

21 Claims, 14 Drawing Sheets